

2424 Evaporative Light Scattering Detector

The Waters® 2424 Evaporative Light Scattering (ELS) Detector with its compact and innovative design offers nearly universal detection of non-volatile and semi-volatile sample components. The 2424 ELS Detector is compatible with both isocratic and gradient separations with nebulizer options to cover a wide range of analytical and microbore flow rates. By adding the orthogonality of ELS to your detection strategy, you increase peak detection confidence across a wide application space.



OPERATING SPECIFICATIONS

Nebulizers

High-flow rate (standard with detector)	300 to 3000 µL/min, (gas flow at 1.80 L/min at 25 psi)
Optional low-flow rate	50 to 500 µL/min, (gas flow at 0.77 L/min at 25 psi)

Temperature control

Nebulizer heater power	0% to 100%
Nebulizer cooler	On/off
Drift tube	Ambient +5.0 to 100.0 °C; 0.1 °C increments
Optional external column heater	Ambient +5.0 to 150.0 °C; 1.0 °C increments

Gas supply	Nitrogen, to be supplied at least 65 psi
------------	--

Gain setting	0 to 1000
--------------	-----------

Filter time constant	Hamming, 0.0 to 5.0 s
----------------------	-----------------------

Sampling rate	Up to 80 points/s
---------------	-------------------

Measurement range	0.1 to 2000.0 LSU
-------------------	-------------------

OPTICAL COMPONENT SPECIFICATIONS

Optics	Heated optics bench (constant 50 °C)
--------	--------------------------------------

Light source	Tungsten halogen polychromatic front mounted, pre-aligned, user installable Warranty: 2000 hours or 1 year warranty (whichever comes first)
--------------	--

Detector	Photomultiplier tube
----------	----------------------

Scattering angle	60 degrees
------------------	------------

Wetted materials	316 stainless steel, aluminum, viton, PTFE, FEP, silicone rubber, polyethylene, polyurethane
------------------	--

ELECTRICAL SPECIFICATIONS

Power requirements	100 to 240 VAC
Line frequency	50 to 60 Hz
Power consumption	200 VA (nominal)
Inputs	4 event inputs
Outputs	4 outputs (2 analog and 2 event)

PHYSICAL/ENVIRONMENTAL SPECIFICATIONS

Dimensions	Width: 34.3 cm (13.5 inches)
	Height: 20.8 cm (8.2 inches)
	Depth: 61.0 cm (24.0 inches)
Weight	18.6 kg (41.0 pounds)
Operating humidity range	20% to 80%, non-condensing
Operating temperature range	4 to 30 °C (39 to 86 °F)
Audible noise	<58 dBA

ORDERING INFORMATION**PART NUMBER**

2424 Evaporative Light Scattering Detector for Alliance® HPLC Systems (high-flow nebulizer included)	176242401
2424 Evaporative Light Scattering Detector for ACQUITY® Arc™ Systems (high-flow nebulizer included)	176017010
High-flow nebulizer	205001124
Low-flow nebulizer	205001125
Column Heating Compartment	WAT038040

Waters

THE SCIENCE OF WHAT'S POSSIBLE.®

Waters, ACQUITY, Alliance, Empower, MassLynx, and The Science of What's Possible are registered trademarks of Waters Corporation. ACQUITY Arc is a trademark of Waters Corporation. All other trademarks are the property of their respective owners.

©2015 Waters Corporation. Produced in the U.S.A. June 2015 720004515EN LM-PDF

Waters Corporation
 34 Maple Street
 Milford, MA 01757 U.S.A.
 T: 1 508 478 2000
 F: 1 508 872 1990
www.waters.com