

ACQUITY UPLC I-Class PLUS System (SM-FTN-I)

The Waters™ ACQUITY™ UPLC™ I-Class PLUS System's holistic design is targeted for investigative analysis where maximized peak capacity, throughput, and sensitivity are critical and is perfectly suited for running any MS-based applications. The system is comprised of a Binary Solvent Manager (BSM) and a Sample Manager with Flow-Through Needle (SM-FTN-I); this configuration offers excellent carryover performance.

ACQUITY UPLC I-CLASS PLUS SYSTEM FEATURES (WITH SM-FTN-I)

Total system bandspread,† 5σ	≤9 μL (default configuration)
Dwell volume (total system)†	≤100 μL (default configuration)
Gradient delay volume†	≤80 μL
Integrated leak management	Leak sensors, as standard, and safe leak handling
System synchronization	Injection synchronization between both pumps and the sample manager enhances retention time reproducibility
Operating flow rate range	0.001 to 2.000 mL/min, in 0.001 mL increments (firmware version 1.71 and later)
Maximum operating pressure	18,000 psi up to 1 mL/min, 12,000 psi up to 2 mL/min
pH range†	1 to 12.5
Unattended operation	Leak sensors, full 96-hour diagnostic data display through console software
Cycle time	≤15 s inject to inject, with load ahead enabled

BINARY SOLVENT MANAGER (BSM)

Number of solvents	Up to four, in combination of two, A1 or A2 and B1 or B2
Solvent conditioning	Integrated vacuum degassing, six lines with two allocated for the injector needlewash/purge solvents
Gradient formation	High pressure mixing, binary gradient
Gradient profiles	11 gradient curves (including linear, step [2], concave [4], and convex [4])
Primary check valves	Intelligent Intake Valves (<i>i</i> ² Valve)
Flow accuracy†	±1.0% of set flow rate at 0.500 mL/min, as per SystemsQT™
Flow precision†	≤0.075% RSD or 0.01 min SD, (0.2 to 2.0 mL/min), whichever is greater using premixed solvent
Composition ripple†	≤1.0 mAu
Composition precision†	≤0.15% RSD or ±0.01 min SD, whichever is greater
Composition accuracy†	±0.5% absolute from 5% to 95%, 0.2 to 2.0 mL/min

Pressure pulsation†	≤0.4% or 25 psi, whichever is greater
Compressibility compensation	Automatic, no user intervention required
Priming	Wet priming runs at a flow rate of 4 mL/min
Pump seal wash	Equipped with a programmable active wash system to flush the rear of the high pressure seals and the plungers
Flow ramping	Automatic
Primary wetted materials	316L stainless steel, UHMWPE blend, MP35N, titanium alloy, gold, sapphire, ruby, zirconia, Nitronic 60, DLC, fluoropolymer, PEEK, PEEK blend
Mixing options	Standard: 50 µL Optional: 100 µL and 380 µL

SAMPLE MANAGER-FTN (SM-FTN-I)

Injection volume range	0.1 to 10.0 µL as standard configuration Up to 1000.0 µL with optional extension loop
Accuracy	±0.2 µL, measured by fluid weight removed from vial with 10.0 µL injections averaged over 20 injections using standard 100-µL syringe
Precision†	≤0.25%, 5 to 50µl
Linearity†	≥0.999
Maximum sample capacity	Any two of the following: <ul style="list-style-type: none"> ▪ 96 and 384 microtiter plates ▪ 48 position 2.00-mL vial plates ▪ 48 position 0.65-mL micro-centrifuge tube plates ▪ 24 position 1.50-mL micro-centrifuge tube plates
Sample compartment temperature range	4.0 to 40.0 °C, settable in 0.1 °C increments; maintains 19 °C below ambient with a tolerance range between -2 and +4 °C
Temperature accuracy	±0.5 °C at sensor
Temperature stability	±1.0 °C at sensor
Sample manager heat time	≤30 min ambient-40 °C
Sample manager cool time	≤60 min ambient-4 °C
Injection needle wash	Integrated, active, programmable
Minimum sample required	3 µL residual, using Waters' Total Recovery 2-mL Vials (zero offset)
Sample carryover†	≤0.001% caffeine (UV) ≤0.001% sulphadimethoxine (MS)
Advanced sample manager capabilities	Auto-dilution and auto-addition
Primary wetted materials	316L stainless steel, polyimide, PEEK blend, DLC, PPS

COLUMN HEATERS (CH-A)

Column capacity	CH-A: Single column, up to 4.6 mm internal diameter (I.D.), up to 150 mm in length with filter or guard column. Mounting extends out for use with MS-based detector
Fittings	18,000 psi, low dispersion, with reusable column inlet fittings
Column compartment temperature range	Settable from 20.0 to 90.0 °C, settable in 0.1 °C increments
Column compartment temperature accuracy	±0.5 °C at sensor
Column compartment temperature stability	±0.3 °C at sensor
Column compartment heat time	≤15 min ambient-60 °C
Solvent conditioning	Active pre-heating as standard; passive pre-heating (for legacy method support)
Column tracking	eCord™ Technology column information management tracks and archives column usage history

COLUMN MANAGEMENT (CM-A)

Column capacity	CM-A: Two columns, as standard (maximum length of 150 mm with filter or guard column) up to 4.6 mm internal diameter (I.D.)
Switching valves	Two nine-port, eight-position valves (CM-A only); provides programmable access switching, waste and bypass positions for rapid solvent changeover
Column compartment(s) temperature range	4.0 to 90.0 °C, settable in 0.1 °C increments; two independent heat/cool zones
Column compartment(s) temperature accuracy	±0.5 °C at sensor
Column compartment(s) temperature stability	±0.3 °C at sensor
Column compartment heat time	≤15 min ambient-60 °C
Column compartment cool time	≤15 min 60–20 °C
Solvent conditioning	Active pre-heating as standard; passive pre-heating (for legacy method support)
Fittings	18,000 psi, low dispersion, with reusable column inlet fittings
Column tracking	eCord Technology column information management tracks and archives column usage history
2D support	Optional

SAMPLE ORGANIZER

Sample plate capacity	Sample plate capacity is configured based on the types and combinations of plates being used: <ul style="list-style-type: none"> ▪ Maximum of 19 standard microtiter plates, up to 15.5 mm high, or ▪ Maximum of 9 intermediate height plates (or 2-mL vial holders), up to 40.0 mm high, or ▪ Maximum of 6 deep well plates (or 4-mL vial holders), up to 47.0 mm high
Maximum sample capacity	Maximum of 7296 samples in nineteen 384-well plates
Sample compartment temperature range	4.0 to 40.0 °C, settable in 0.1 °C increments with a tolerance range between -2 and +4 °C
Temperature accuracy	±1 °C at the sensor
Temperature stability	±1 °C at the sensor

BASED INSTRUMENTAL CONTROL

External control	Empower™ Software, MassLynx™ Software, UNIFI™ Scientific Information System, or standalone through console software
External communications	Ethernet interfacing via RJ45 connection to host PC
Event inputs/outputs	Rear panel contact closure and/or TTL inputs/outputs
Connections INSIGHT™	Provides real-time monitoring and automatic notification of instrument performance and diagnostic information, allowing for quicker problem resolution

ENVIRONMENTAL SPECIFICATIONS

Acoustic noise	≤62 dBA, system
Humidity operating	20% to 80%, non-condensing
Operating temperature range	4 to 40 °C

ELECTRICAL SPECIFICATIONS

Power requirements	100 to 240 VAC
Line frequency	50 to 60 Hz
Power consumption	BSM: 360 VAC FTN: 400 VAC CM-A: 400 VAC

PHYSICAL SPECIFICATIONS

ACQUITY UPLC I-Class PLUS System: Width: 34.3 cm (13.5 in.)
BSM, SM-FTN-I, and CH-A Height: 71.1 cm (28.0 in.)
Depth: 71.2 cm (28.0 in.)

ACQUITY UPLC I-Class PLUS System: Width: 34.3 cm (13.5 in.)
BSM, SM-FTN-I, and CM-A Height: 79.6 cm (31.4 in.)
Depth: 71.2 cm (28.0 in.)

Sample Organizer Width: 25.4 cm (10.0 in.)
Height: 96.5 cm (38.0 in.)
Depth: 71.1 cm (28.0 in.)

† For specific test conditions, contact your Waters sales representative.

Waters

THE SCIENCE OF WHAT'S POSSIBLE.™

Waters, The Science of What's Possible, ACQUITY, UPLC, eCord, Empower, MassLynx, SystemsQT, UNIFI, and Connections INSIGHT are trademarks of Waters Corporation. All other trademarks are the property of their respective owners.

©2018 Waters Corporation. Produced in the U.S.A. April 2018 720006149EN LM-PDF

Waters Corporation
34 Maple Street
Milford, MA 01757 U.S.A.
T: 1 508 478 2000
F: 1 508 872 1990
www.waters.com